

What is claimed is:

1. A receiving circuit comprising:
- an antenna and a radio unit for receiving a signal transmitted via a radio link;
- a plurality of finger receivers for inversely diffusing the signal received by the antenna and the radio unit in association with respective multiple paths;
- a synthesizer for synthesizing signals inversely diffused by said finger receivers; and
- means for controlling a number of finger receivers to operate, among said plurality of finger receivers, based on whether or not a speech signal or data is contained in the signal received by the antenna and the radio unit.

- Sub A
- 5 A receiving circuit according to claim 1, further comprising means for controlling a number of finger receivers to operate if a speech signal or data is not contained in the signal received by the antenna and the radio unit, based on a number of base stations which are communicating with the receiving circuit.

3. A receiving circuit according to claim 1, further comprising means for controlling a number of finger receivers to operate if a speech signal or data is not contained in the signal received by the antenna and

5 the radio unit, based on whether the receiving circuit is in a soft hand-over mode or not.

4. A receiving circuit according to claim 3, further comprising means for operating as many finger receivers as a number of base stations which are communicating with the receiving circuit if the receiving
5 circuit is in the soft hand-over mode, and operating a minimum number of finger receivers required to detect whether or not a speech signal or data is contained in the signal received by the antenna and the radio unit, if the receiving circuit is not in the soft hand-over mode.

5. A receiving circuit according to claim 1, further comprising means for controlling the number of finger receivers to operate by controlling a supply of a clock signal to said plurality of finger receivers.

6. A receiving circuit according to claim 2, further comprising means for controlling the number of finger receivers to operate by controlling a supply of a clock signal to said plurality of finger receivers.

7. A receiving circuit according to claim 3, further comprising means for controlling the number of finger receivers to operate by controlling a supply of a

552250-40240
Cont.

Al Cont
clock signal to said plurality of finger receivers.

8. A receiving circuit according to claim 4, further comprising means for controlling the number of finger receivers to operate by controlling a supply of a clock signal to said plurality of finger receivers.

9. A receiving circuit comprising:
an antenna and a radio unit for receiving data;
a plurality of finger receivers for inversely
diffusing the data received by the antenna and the radio
5 unit in association with respective multiple paths;
a synthesizer for synthesizing signals
inversely diffused by said finger receivers;
detecting means for detecting whether there is
a speech signal or not based on the data inversely
10 diffused by said finger receivers; and
control means for controlling a number of
finger receivers to operate, among said plurality of
finger receivers, based on a detected result from said
detecting means.

10. A receiving circuit according to claim 9, wherein said control means comprises means for operating all the finger receivers if a speech signal is detected by said detecting means.

11. A receiving circuit according to claim 9,
wherein at least one of said finger receivers is operated
at all times without being controlled by said control
means, and said detecting means comprises means for
5 detecting whether there is a speech signal or not based
on data inversely diffused by said at least one of the
finger receivers.

12. A receiving circuit according to claim 10,
wherein at least one of said finger receivers is operated
at all times without being controlled by said control
means, and said detecting means comprises means for
5 detecting whether there is a speech signal or not based
on data inversely diffused by said at least one of the
finger receivers.

13. A receiving circuit according to claim 9,
wherein at least two of said finger receivers are
operated at all times without being controlled by said
control means, and said detecting means comprises means
5 for detecting whether there is a speech signal or not
based on data inversely diffused by said at least two of
the finger receivers.

14. A receiving circuit according to claim 10,

wherein at least two of said finger receivers are operated at all times without being controlled by said control means, and said detecting means comprises means
5 for detecting whether there is a speech signal or not based on data inversely diffused by said at least two of the finger receivers.

15. A receiving circuit according to claim 9, wherein said detecting means comprises a plurality of detecting means associated with said plurality of finger receivers, respectively.

16. A receiving circuit according to claim 10, wherein said detecting means comprises a plurality of detecting means associated with said plurality of finger receivers, respectively.

17. A receiving circuit according to claim 15, wherein said control means comprises means for operating, at all times, one of said plurality of finger receivers which has a highest correlated value, and controlling
5 operation of other finger receivers based on a detected result from the detecting means associated with said one of the finger receivers.

18. A receiving circuit according to claim 16,

wherein said control means comprises means for operating,
at all times, one of said plurality of finger receivers
which has a highest correlated value, and controlling
5 operation of other finger receivers based on a detected
result from the detecting means associated with said one
of the finger receivers.

19. A receiving circuit according to claim 9,
wherein said detecting means comprises two detecting
means associated respectively with two of said plurality
of finger receivers, and said control means comprises
5 means for operating the two finger receivers associated
with said two detecting means at all times irrespective
of detected results from said detecting means and
controlling operation of other finger receivers based on
the detected results from said detecting means if the
10 receiving circuit is in a hand-over mode, and operating
one of the two finger receivers associated with said two
detecting means at all times irrespective of detected
results from said detecting means and controlling
operation of other finger receivers based on the detected
15 results from said detecting means if the receiving
circuit is not in the hand-over mode.

20. A receiving circuit according to claim 10,
wherein said detecting means comprises two detecting

means associated respectively with two of said plurality
of finger receivers, and said control means comprises
5 means for operating the two finger receivers associated
with said two detecting means at all times irrespective
of detected results from said detecting means and
controlling operation of other finger receivers based on
the detected results from said detecting means if the
10 receiving circuit is in a hand-over mode, and operating
one of the two finger receivers associated with said two
detecting means at all times irrespective of detected
results from said detecting means and controlling
operation of other finger receivers based on the detected
15 results from said detecting means if the receiving
circuit is not in the hand-over mode.

21. A receiving circuit according to claim 15,
wherein said control means comprises means for operating,
at all times, two of said plurality of finger receivers
which have a highest correlated value irrespective of
5 detected results from said detecting means, and
controlling operation of other finger receivers based on
detected results from the detecting means associated with
said two of the finger receivers, if the receiving
circuit is in a hand-over mode, and operating, at all
10 times, one of said plurality of finger receivers which
has a highest correlated value irrespective of detected

results from said detecting means, and controlling
operation of other finger receivers based on a detected
result from the detecting means associated with said one
15 of the finger receivers, if the receiving circuit is not
in the hand-over mode.

22. A receiving circuit according to claim 16,
wherein said control means comprises means for operating,
at all times, two of said plurality of finger receivers
which have a highest correlated value irrespective of
5 detected results from said detecting means, and
controlling operation of other finger receivers based on
detected results from the detecting means associated with
said two of the finger receivers, if the receiving
circuit is in a hand-over mode, and operating, at all
10 times, one of said plurality of finger receivers which
has a highest correlated value irrespective of detected
results from said detecting means, and controlling
operation of other finger receivers based on a detected
result from the detecting means associated with said one
15 of the finger receivers, if the receiving circuit is not
in the hand-over mode.

23. A receiving circuit comprising:

an antenna and a radio unit for receiving data;
a plurality of finger receivers for inversely

diffusing the data received by the antenna and the radio
5 unit in association with respective multiple paths;

a synthesizer for synthesizing signals
inversely diffused by said finger receivers;

a decoder for decoding the data synthesized by
said synthesizer;

10 detecting means for detecting whether there is
a speech signal or not based on the data decoded by said
decoder; and

control means for controlling a number of
finger receivers to operate, among said plurality of
15 finger receivers, based on a detected result from said
detecting means.

24. A receiving circuit according to claim 23,
wherein said control means comprises means for operating
all the finger receivers if a speech signal is detected
by said detecting means.

25. A receiving circuit according to claim 23,
wherein said control means comprises means for operating,
at all times, one of said plurality of finger receivers
which has a highest correlated value.

26. A receiving circuit according to claim 24,
wherein said control means comprises means for operating,

at all times, one of said plurality of finger receivers which has a highest correlated value.

27. A receiving circuit according to claim 9, wherein said control means comprises means for controlling operation of said plurality of finger receivers by controlling a supply of a clock signal to
5 said plurality of finger receivers.

28. A receiving circuit according to claim 15, wherein said control means comprises means for controlling operation of said plurality of finger receivers by controlling a supply of a clock signal to
5 said plurality of finger receivers.

29. A receiving circuit according to claim 23, wherein said control means comprises means for controlling operation of said plurality of finger receivers by controlling a supply of a clock signal to
5 said plurality of finger receivers.

30. A mobile terminal having a receiving circuit according to claim 1.

31. A mobile terminal having a receiving circuit according to claim 5.

32. A mobile terminal having a receiving circuit according to claim 9.

33. A mobile terminal having a receiving circuit according to claim 15.

34. A mobile terminal having a receiving circuit according to claim 23.

35. A mobile terminal having a receiving circuit according to claim 27.

36. A method of receiving data by inversely diffusing a signal received by an antenna and a radio unit with a plurality of receivers of a receiving circuit in association with respective multiple paths, synthesizing inversely diffused signals, and outputting a synthesized signal, comprising the step of:

controlling a number of receivers to operate, among said plurality of receivers, based on whether or not a speech signal or data is contained in the signal received by the antenna and the radio unit.

37. A method according to claim 36, further comprising the step of controlling the number of

receivers to operate if a speech signal or data is not
contained in the signal received by the antenna and the
5 radio unit, based on a number of base stations which are
communicating with the receiving circuit.

38. A method according to claim 36, further
comprising the step of controlling the number of
receivers to operate if a speech signal or data is not
contained in the signal received by the antenna and the
5 radio unit, based on whether a receiving circuit is in a
soft hand-over mode or not.

39. A method according to claim 38, further
comprising the steps of:

operating as many finger receivers as a number
of base stations which are communicating with the
5 receiving circuit if the receiving circuit is in the soft
hand-over mode; and

operating a minimum number of finger receivers
required to detect whether or not a speech signal or data
is contained in the signal received by the antenna and
10 the radio unit, if the receiving circuit is not in the
soft hand-over mode.

40. A method according to claim 36, further
comprising the step of controlling the number of

receivers to operate by controlling a supply of a clock signal to said plurality of receivers.

41. A method according to claim 37, further comprising the step of controlling the number of receivers to operate by controlling a supply of a clock signal to said plurality of receivers.

42. A method according to claim 38, further comprising the step of controlling the number of receivers to operate by controlling a supply of a clock signal to said plurality of receivers.

43. A method according to claim 39, further comprising the step of controlling the number of receivers to operate by controlling a supply of a clock signal to said plurality of receivers.

44. A method of receiving data by inversely diffusing data received by an antenna and a radio unit with a plurality of receivers of a receiving circuit in association with respective multiple paths, synthesizing
5 inversely diffused data, and outputting synthesized data, comprising the steps of:

detecting whether there is a speech signal or not based on the inversely diffused data; and

controlling a number of receivers to operate,
10 among said plurality of receivers, based on a detected
result of whether there is a speech signal or not.

45. A method according to claim 44, further
comprising the step of operating all the receivers if a
speech signal is detected.

46. A method according to claim 44, further
comprising the step of operating at least one of said
plurality of receivers at all times.

47. A method according to claim 45, further
comprising the step of operating at least one of said
plurality of receivers at all times.

48. A method according to claim 44, further
comprising the step of operating at least two of said
plurality of receivers at all times.

49. A method according to claim 45, further
comprising the step of operating at least two of said
plurality of receivers at all times.

50. A method according to claim 44, further
comprising the step of operating, at all times, one of

said plurality of receivers which has a highest correlated value.

51. A method according to claim 45, further comprising the step of operating, at all times, one of said plurality of receivers which has a highest correlated value.

52. A method according to claim 44, further comprising the steps of:

operating at least two of said receivers at all times if the receiving circuit is in a hand-over mode;

5 and

operating one of said receivers at all times if the receiving circuit is not in the hand-over mode.

53. A method according to claim 45, further comprising the steps of:

operating at least two of said receivers at all times if the receiving circuit is in a hand-over mode;

5 and

operating one of said receivers at all times if the receiving circuit is not in the hand-over mode.

54. A method according to claim 52, further comprising the steps of:

operating two of said receivers which have a highest correlated value at all times if the receiving circuit is in the hand-over mode; and

operating one of said receivers which has a highest correlated value at all times if the receiving circuit is not in the hand-over mode.

55. A method of receiving data by inversely diffusing data received by an antenna and a radio unit with a plurality of receivers of a receiving circuit in association with respective multiple paths, synthesizing inversely diffused data, decoding synthesized data, and outputting decoded data, comprising the steps of:

detecting whether there is a speech signal or not based on the decoded data; and

controlling a number of receivers to operate, among said plurality of receivers, based on a detected result of whether there is a speech signal or not.

56. A method according to claim 55, further comprising the step of operating all the receivers if a speech signal is detected.

57. A method according to claim 55, further comprising the step of operating, at all times, one of said plurality of receivers which has a highest

correlated value.

58. A method according to claim 56, further comprising the step of operating, at all times, one of said plurality of receivers which has a highest correlated value.

59. A method according to claim 44, further comprising the step of controlling operation of said plurality of receivers by controlling a supply of a clock signal to said plurality of receivers.

60. A method according to claim 45, further comprising the step of controlling operation of said plurality of receivers by controlling a supply of a clock signal to said plurality of receivers.

61. A method according to claim 52, further comprising the step of controlling operation of said plurality of receivers by controlling a supply of a clock signal to said plurality of receivers.

62. A method according to claim 55, further comprising the step of controlling operation of said plurality of receivers by controlling a supply of a clock signal to said plurality of receivers.

63. A method according to claim 56, further comprising the step of controlling operation of said plurality of receivers by controlling a supply of a clock signal to said plurality of receivers.

Add A3

552250 40240460